

Spud Positioning Pontoon Naseem



PRINCIPAL CHARACTERISTICS

Name	Naseem
Type	Flat Top Barge with spuds
Year of construction	2006
Owner	Middle East Dredging Company Q.S.C.
Classification Society	American Bureau of Shipping
Length overall	100.58 m
Breadth overall	30.48 m
Moulded depth	6.10 m
Draught unloaded / loaded	1.10 m / 4.74 m
Gross tonnage	4847

MEDCO
MIDDLE EAST DREDGING COMPANY

شركة الشرق الأوسط للجرف

P.O. Box 24745, 4th floor, Al Fardan Plaza
Al Sadd Street, Doha – State of Qatar
Tel: (+974) 442 67 62 - Fax: (+974) 442 67 52

Spud Positioning Pontoon Naseem

Net tonnage	1454
Permissible deck loading	15t/m ²
DWT	11,197MT
Spuds :	2 units
Diameter	1220mm
Length	23m
Hydraulic Winches :	4 x 50t, remote control 2 units for spuds, 2 units for ramps
Hydraulic Power pack :	HYCOS Caterpillar C9 ACERT, 242 KW
Generator :	??
Ramps :	2 units – 6m wide x 12m long
Bunker capacity :	
Diesel Fuel Oil	22 m ³
Potable water	22 m ³
Accommodation :	1 unit office cabin 1 unit shower/toilet cabin 2 units store container 1 unit lunchroom

